

Starfloor Click 30 & 30 Plus

Datasheet

Classification	Norm	Tarkett Value
Product type	EN ISO 10582	Heterogeneous poly(vinyl chloride) floor coverings
Domestic classification	EN ISO 10874	23 Heavy
Commercial classification	EN ISO 10874	31 Moderate
Technical Characteristics	Norm	Tarkett Value
Total thickness	EN ISO 24346	4 mm
Wear layer thickness	EN ISO 24340	0,30 mm
Total weight	EN ISO 23997	7400 g/m ²
Binder content	EN ISO 10582	Type I
Surface treatment		PUR Extreme
Embossing in Register		Yes
Bevelled edges		2 sides
Installation method		Click
Performance for CE Marking	Norm	Tarkett Value
Declaration of Performance #	EN 14041	0131-0035-DoP-2013-07
Technical Performance	Norm	Tarkett Value
Dimensional stability	EN ISO 23999	Average measured value : ≤ 0.10 %
Curly resultant to heat	EN ISO 23999	≤ 1 mm
Reaction to fire	EN 13501-1	Bfl-s1
Residual indentation	EN ISO 24343-1	Required value: ≤ 0,10 mm
Furniture leg	EN ISO 16581	No damage
Castor chair	EN ISO 4918	No damage
Impact sound reduction - ΔLw	EN ISO 717-2	3 dB
Reduction of in-room impact noise	NF S31-074	Class C (≤ 85 dB)
Thermal resistance	EN ISO 10456	0,03 m ² •K/W
Colour fastness to light	EN ISO 105-B02	≥ 6
Chemical resistance	EN ISO 26987	Good resistance
Slip resistance	DIN 51130	R10
Slip resistance	EN 13893	Class DS (μ ≥ 0,30)
Peeling Resistance	EN ISO 24345	≥ 50N/50mm
Static Electrical Propensity	EN 1815	Antistatic (≤ 2 kV)
Underfloor heating		Suitable (maximum 27°C)
Sustainability performances	Norm	Tarkett Value
Total VOC Emissions	EN 16516	Gold (≤ 100 μg / m ³)
Recyclability through ReStart®		Recyclable
Phthalate - free		Yes
Dimensions and designs		
Plank	Plank 183 x 1222 mm - 9 planks=2,009 m ² /box - 60 boxes/pallet	
Tile	Tile 310 x 601 mm - 9 tiles=1,675 m ² /box - 76 boxes/pallet Tile 310 x 603 mm - 9 tiles=1,682 m ² /box - 76 boxes/pallet	
Number of designs available	30	

Embossing in register : On Authentics references

Installation Brief:

Edge joints in damp rooms of max. 12 m², e.g. bathrooms or kitchens, may be made with silicone in order to avoid any infiltration of water through the expansion joint and onto the installed surface. For all larger areas in damp rooms, we recommend starting by applying insulating tape to the area of the joint before filling it with a quantity of silicone and/or using a skirting board with a sealing lip.



The above information is subject to modification for the benefit of further improvement (16/03/2022). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website <https://www.tarkett.com>. Tarkett's instructions regarding installation, cleaning and maintenance should be observed.

Please contact Tarkett at the address shown for the instructions.